




## CONIC DESK


Its angled leg is the hallmark of the Conic desk. Through their lightweight design, the legs accompany the organic shapes of the work top to give a homogeneous visual aesthetic to the entire assembly. The high quality with which the joints are solved make this programme a first-class solution for the work environment.



### OPTIONAL FEATURES


#### MODESTY PANEL

- 0.8-mm thick steel
- 16-mm thick melamine



#### TRAY

- 0.8-mm thick metal
- With flip-open cover or cable grommet.
- As individual desk or return.




ABS side covers in white (BA) with white (BA) structure. In black (NE) for other structure colours.

#### CABLE MANAGEMENT CHANNEL

- Single, hinged



- Double with 2 height positions





ABS side covers in white (BA) with white (BA) structure. In black (NE) for other structure colours.



### OPTIONAL FEATURES

#### CHANNEL ACCESSES

- Metal flip-open cover \*\*  
2-mm perimeter in black (NE)  
Built-in sockets option
- Melamine flip-open cover  
2-mm perimeter in black (NE)  
Same finish as work top  
Built-in sockets option



- Ø60 cable grommet \*  
White (BA) and black (NE)




- Ø60 multi-connection socket \*\*  
White (BA) and black (NE)  
1 power socket + 1USB A + 1USB C  
+ 20 cm cable ending in Wieland connector



\* White (BA) access: White (BA) work top • Black (NE) access: Other work tops




\*\* As per order

Positioning:



#### CABLE RISER

- Mesh to channel
- Jointed to channel
- Totem to floor
- Access cover on middle leg



1-mm thick painted sheet metal

INDIVIDUAL WORK STATION

GROUP WORK STATION



## CONIC DESK



### DESCRIPTION

#### WORK TOP

Top made of 25-mm thick chipboard bonded with synthetic resins, especially designed for applications that require high bending strength. Average density: 620/595 kg/m<sup>3</sup> as per EN 323.

Laminate finish. 2-mm thick ABS edge as per UNE 56.843:01.

Single work top on face-to-face work stations.

The return can be fitted on either the right or left of the main desk.

#### STRUCTURE




Metal frame built with two 1.5-mm thick 50x30 steel profiles as per UNE-EN 10305.

End legs built with 1.5-mm thick 50x30 upper crossbars as per UNE-EN 10305. The legs to the floor are d-50 cylindrical tubes which taper to d-25 mm.

Metal middle leg on the group work stations built with slanted 1.5-mm thick 50x30 vertical profiles and two 1.5-mm thick 50x30 profiles as per UNE-EN 10305 welded to the leg.

60/80µm epoxy powder in compliance with current reaction to fire standard UNE 23827-90.

Leg levelling: 20 mm




# TECHNICAL SHEET



### DETAILS



▲ FLIP-OPEN COVER  
Metal



▲ FLIP-OPEN COVER  
Melamine  
Same finish as work top



▲ CHANNEL ACCESS  
Ø60 multi-connection  
socket



▲ CHANNEL  
Double



▲ CHANNEL  
Single, hinged



▲ MIDDLE LEG



### CERTIFICATES






# CONIC DESK

# TECHNICAL SHEET




## RANGE

### INDIVIDUAL DESK




F \ W	80	100	120	140	160	180	200
60	●	●	●	●	●	●	●
70	●	●	●	●	●	●	●
80	●	●	●	●	●	●	●
100		●	●	●	●	●	●

### RETURN




F \ W	80	100	120
60	●	●	●

### BENCH




F \ W	120	140	160	180	200
120	●	●	●	●	●
140	●	●	●	●	●
160	●	●	●	●	●

### DESK IN ROWS




F \ W	80	100	120	140	160	180	200
60	●	●	●	●	●	●	●
70	●	●	●	●	●	●	●
80	●	●	●	●	●	●	●

### CELL



F \ W	120	135	140
LEFT	●	●	●
RIGHT	●	●	●



KEY
PRICE TERMS
● GENERAL
● EXPRESS