




VIRA DESK


With its slanted wooden or metal legs as its hallmark and harmonious finishes, the friendly shapes of this work desk-cum-table follow the aesthetic of the current market.



OPTIONAL FEATURES


MODESTY PANEL

- 0.8-mm thick metal
- 16-mm thick melamine



TRAY


- 0.8-mm thick steel
- For flip-open cover or cable grommet




ABS side covers in white (BA) with white (BA) structure. In black (NE) for other structure colours.

CABLE MANAGEMENT CHANNEL

- Single, hinged



- Double with 2 height positions



ABS side covers in white (BA) with white (BA) structure. In black (NE) for other structure colours.



* White (BA) cover: White (BA) structure • Black (NE) cover: Other structures



OPTIONAL FEATURES

CHANNEL ACCESSES

- Metal flip-open cover **
2-mm perimeter in black (NE)
Built-in sockets option
- Melamine flip-open cover
2-mm perimeter in black (NE)
Same finish as work top
Built-in sockets option



- Ø 60 cable grommet *
Colour: white (BA) and black (NE)




- Ø 60 multi-connection socket **
White (BA) and black (NE)
1 power socket + 1USB A + 1USB C
+ 20cm cable ending in Wieland connector



* White (BA) access: White (BA) work top • Black (NE) access: Other work tops


** As per order

Positioning:



CABLE RISER


- Mesh to channel




- Jointed to channel



- Totem to floor



- Access cover on middle leg



1-mm thick painted sheet metal

INDIVIDUAL WORK STATION

GROUP WORK STATION

www.dynamobel.com



VIRA DESK



DESCRIPTION

WORK TOP

Top made of 25-mm thick chipboard bonded with synthetic resins, especially designed for applications that require high bending strength. Average density: 620/595 kg/m³ as per EN 323.

Laminate finish. 2-mm thick ABS edge as per UNE 56.843:01.

Single work top on face-to-face work stations.

The return can be fitted on either the right or left of the main desk.

STRUCTURE




Metal frame built with two 1.5-mm thick 50x30 steel profiles as per UNE-EN 10305.

End legs built with 1.5-mm thick 50x30 upper crossbars as per UNE-EN 10305 and legs to the floor. Option: 1.5-mm thick shaped sheet metal or in oak veneered beech wood.

Metal middle leg on the group work stations built with slanted 1.5-mm thick 50x30 vertical profiles and two 1.5-mm thick 50x30 profiles as per UNE-EN 10305 welded to the leg.

60/80µm epoxy powder in compliance with current reaction to fire standard UNE 23827-90.

Leg levelling: 20 mm




TECHNICAL SHEET



DETAILS



▲ FLIP-OPEN COVER
Metal



▲ FLIP-OPEN COVER
Melamine
Same finish as work top



▲ CHANNEL ACCESS
Ø 60 multi-connection
socket



▲ CHANNEL
Double



▲ CHANNEL
Single, hinged



▲ MIDDLE LEG



CERTIFICATES






VIRA DESK

TECHNICAL SHEET




RANGE

INDIVIDUAL DESK




RETURN



	80	100	120
60	●	●	●


	80	100	120	140	160	180	200
60	●	●	●	●	●	●	●
70	●	●	●	●	●	●	●
80	●	●	●	●	●	●	●
100		●	●	●	●	●	●

DESK IN ROWS




	80	100	120	140	160	180	200
60	●	●	●	●	●	●	●
70	●	●	●	●	●	●	●
80	●	●	●	●	●	●	●

BENCH




	120	140	160	180	200
120	●	●	●	●	●
140	●	●	●	●	●
160	●	●	●	●	●

CELL



	120	135	140
LEFT	●	●	●
RIGHT	●	●	●



KEY

PRICE TERMS
● GENERAL
● EXPRESS