



## VIVA MEETINGS


A wide range of sizes, heights and table-top shapes make this table the best choice to blend in anywhere. Its clean, well-defined lines reduce this table to the minimal expression and make it functional and timeless at the same time.





### OPTIONAL FEATURES

#### CHANNEL ACCESSES

- **Central flip-open cover**  
Metal or same finish as work top  
2-mm perimeter in black  
Built-in sockets option



- **Polyamide flip-open cover**  
Colour: white (BA) and black (NE)



Metal channel when there is a flip-open cover.

- **Ø 60 / Ø 80 cable grommet**  
Colour: white (BA) and black (NE)



- **Ø 80 multi-connection socket**  
Colour: white (BA) and black (NE)  
1 power socket + 1USB C + 1m cable ending in Wieland connector



- **Ø 60 multi-connection socket**  
Colour: white (BA) and black (NE)  
1 power socket + 1USB A + 1USB C + 1m cable ending in Schuko connector



# TECHNICAL SHEET



### DESCRIPTION

#### DESK TOP

Top made of 25-mm thick chipboard bonded with synthetic resins, especially designed for applications that require high bending strength. Average density: 620/595 kg/m<sup>3</sup> as per EN 323.





- Laminated finish. 2-mm thick ABS edge as per UNE 56.843:01.
- Finished on top with 0.7-mm thick anti-fingerprint HPL as per the indications of UNE 53173-92 and underneath with balancing sheet (BM80). 2-mm thick ABS edge as per UNE 56.843:01.
- Finished in wood treated with high-resistance varnish. 2-mm thick wood edge.

#### STRUCTURE


Cylindrical metal leg made of 3-mm thick tube with a diameter of 127 mm as per DIN2394 ST44 on tables with diameter > 800 mm and 3-mm thick tube with a diameter of 70 mm DIN2394 ST44 on tables with diameter ≤ 800 mm, with flat bars welded to the top and bottom which screw onto the structure and base.

The base, with 3 spokes on tables with a diameter of 600 to 800 mm and 4 spokes on tables with diameter > 800 mm, is a welded assembly consisting of 2.5-mm thick folded sheet-metal omega profiles (DC01 UNE-EN10130) welded to spokes made of 4-mm thick sheet metal (DC01 UNE-EN10130).


60/80 micras epoxy powder coated that complies with current UNE 23827-90 reaction to fire regulations.



Ø600 / Ø800



Ø1000 / Ø1200



Ø1400 / Ø1600




VIVA  
MEETINGS

# TECHNICAL SHEET




## RANGE

### ROUND TABLE





Ø	60	80
H	74	
	90	
	105	




Ø	100	120	140	160
H	74			

### SQUARE TABLE



W	75
h=74	

### RECTANGULAR TABLE




W	120	180
F	75	

#### KEY


PRICE TERMS  
● GENERAL  
● EXPRESS



## DETAILS



▲ FLIP-OPEN COVER  
Metal



▲ FLIP-OPEN COVER  
Melamine  
Same finish as work top



▲ CHANNEL ACCESS  
Ø 60 multi-connection  
socket



▲ 4-SPOKE BASE



▲ 3-SPOKE BASE



▲ SQUARE BASE



▲ CHANNEL ACCESS  
Ø 80 multi-connection  
socket