

## LINE Wall cover

### Characteristics

#### Dimensions

Standard module width between axes:

- Blind partition: 1200 mm.
- Standard floor/ceiling heights:
  - ° F/C blind partition: 2700 and 3050 mm.
  - ° Blind partition with several panels: 2700, 3050, 3500 and 4500 (only blind B and blind F) mm.

Height tolerance absorption capacity of blind partition:  $\pm 5$  mm.

Partition thickness: from 56 mm to 132 mm.

Weight/m<sup>2</sup>:

- CWith chipboard panels: 25 kg/m<sup>2</sup>.
- With metal panels clad with plasterboard: 30 kg/m<sup>2</sup>.

#### Structure

- Visible profiles and internal structure in Sendzimir galvanised steel.
- Quality according to European standard EN 10346:2009(DX51D+Z).

#### Paintwork

- Previously degreased.
- Electrostatically coated with polyester powder or polyester epoxy and polymerised in furnace at 200°C.
- Average paint coat thickness: 50/90  $\mu$ .
- Colour tolerance measured per DIN 5033.

#### Outer faces, mineral fibre, doors and windows

- Chipboard panels, edged and faced with semi-rigid vinyl, fine hardwood, melamine, lacquered or painted metal finishes Total thickness: 16 mm.
- Inner insulation with semi-rigid, 20-mm thick, 90 kg/m<sup>3</sup> mineral fibre panelling.

#### Fittings

- Metal fittings treated with the same paint, zinc coating, etc. depending on case.

### Demountability, re-installation

- Full, independent demountability of all components thanks to the splice joints which form the grooves on the hidden profiling design.
- The panes can be demounted from the structure independently.

### Dynamobel quality

- All the processes used in the design, production, distribution and sale of DYNAMOBEL's Line demountable partition are quality assurance certified by LLOYD'S per EN ISO 9001:2008.

## LINE Wall cover

### Standard module

