

**dynamobel**

**M92 FUGA**  
MAINTENANCE AND  
CLEANING GUIDE

## M92 FUGA MAINTENANCE AND CLEANING GUIDE

This guide contains the basic information which the customer and/or user needs to know in order to maintain and clean an M92 Fuga demountable partition and achieve greater performance and longer system life.

### 1. MAINTENANCE

This product requires very little maintenance. Most of the work centres on the doors. The handles or knobs may come loose as a result of heavy use and require fixture adjustment. This is very easy and calls for very little skill.

It should also be remembered that double-glazing frames, while ensuring good insulation, are not watertight. For this reason, when assembled in harsh weather conditions, it may be necessary to demount glazed modules after a time in order to clean them inside. The frames are demounted and cleaned following the normal procedure.

### 2. THE CLEANING OF PANELS COATED WITH SEMI-RIGID VINYL AND CELLULOSE- OR COTTON-BACKED VINYL

#### 2.1 Getting rid of small stains

**Product:** Neutral detergent or ammonia.

**Instructions of use:**

- Dilute a small quantity of the cleaning product in warm water (use just ammonia on stubborn stains).
- Apply the solution onto the stain and surrounding area (without rubbing) with a well-wrung sponge or cloth.
- Rinse with water.
- Dry with synthetic duster.

**Note:** Consult cleaning product experts for special stains.

#### 2.2 Regular maintenance of large surfaces

The frequency of cleaning depends on the use the installation is subject to. Cotton-backed vinyl coatings should not be cleaned so often.

Follow the steps described above, leaving the surface to dry once cleaned without using a duster.

## M92 FUGA MAINTENANCE AND CLEANING GUIDE

### 3. THE CLEANING OF WOOD-COATED PANELS

#### Getting rid of small stains

**Product:** Wood cleaning product..

**Instructions of use:**

- Apply the product to the cloth to be used to clean the surface. Never apply the product directly onto the surface as this may produce staining.
- Wipe the surface gently with the damp cloth.
- If product residue remains, wipe with a dry cloth.

### 4. THE CLEANING OF METAL ELEMENTS WITH POLYESTER OR EPOXY POLYESTER POWDER PAINT

#### 4.1 Getting rid of small stains

**Product:** Neutral detergent or ammonia.

**Instructions of use:**

- Dilute a small quantity of the cleaning product in warm water (use just ammonia on stubborn stains).
- Apply the solution onto the stain and surrounding area (without rubbing) with a well-wrung sponge or cloth.
- Rinse with water.
- Dry with synthetic duster.

**Note:** Consult cleaning product experts for special stains.

#### 4.2 Regular maintenance of large surfaces

The frequency of cleaning depends on the use the installation is subject to. Follow the steps described above, leaving the surface to dry once cleaned without using a duster.

## M92 FUGA MAINTENANCE AND CLEANING GUIDE

### 5. THE CLEANING OF GLASS ELEMENTS

#### Getting rid of small stains and regular maintenance

**Product:** ammonia.

**Instructions of use:**

- Dilute a small quantity of the product in warm water.
- Apply the solution to the surface with a damp cloth.
- Leave to dry.

**NOTE:**

Special glass-cleaning products may be used; follow the manufacturer's instructions. These products should be colourless as they may seep between the glass and the excluder, it then being necessary to demount the module to get rid of the stain.

2005