PAD
MEETING AND VISITOR

TECHNICAL SHEETS

FEATURES

1 **Four-legged chair:**
Stackable.
Options:
Linkable.
Castors.
Wirting tablet
Upholstered seat or upholstered seat

Linkable in option

Wirting tablet in option

DIMENSIONS

kg	kg sb / cb	6,40 / 8,80
Ta	Seat fabric	0,70
Tr	Backrest fabric	0,70
Pa	Seat leather	0,84
Pr	Backrest leather	0,84

DESCRIPTION

SEAT AND BACK

Single Shell injection moulded in glass fibre-reinforced polyamide. Its anatomy allows to adjust to the shape of the user's back and force him to a correct sitting position. Rounded seat edge minimizing pressure points on the legs.

In the upholstered version, it will have a seat or back cushion screwed to the shell.

STRUCTURE

High strength steel tube diameter 16*1.5 mm, 4 legs. Joined to the body with welded plates.

The linking element consist in an extractable assembly located beneath the Shell. In two parts:

• A metal part: Ø4 curved chromed rod,

• And another plastic part: injection piece in PA6+30 fiber in black, with over-injected button in red.

ARMS

Steel tube arms with a diameter of 16*1.5 mm, welded to the structure with integral armrests with a soft and rubbery touch.

In the writing tablet version, the arm will be a continuation of the front leg, welded to the structure. tablet in compact GA, 8 mm thickness.

RECYCLABILITY RATE

CERTIFICATIONS AND STANDARDS

UNE-EN 16139