

## Technical characteristics

### Description

- Relocatable, demountable, prefabricated, modular wall storage with interior frame levelling. Designed to complement Dynamobel partition systems.

### Dimensions

- Standard module width between axes:  
600 and 1,200 mm, corner unit: 800 x 800 mm
- Standard heights:
  - Worktop height: 882 mm
  - Door height: 2,082 mm
  - Floor/ceiling heights: 2,700 and 3,100 mm
- Module depths:
  - Without back: 419 mm
  - With hidden back: 432 mm
  - With visible back: 438 mm
- Tolerance absorption capacity:
  - On height:  $\pm 20$  mm
  - On starts: <605 mm

### Outer faces

- Woodchip hardboard panels, PVC edged, rigid or flexible as required and coated with semi-rigid vinyl, cotton-gauze or cellulose-based vinyl, laminates, woods, etc. System 32 machining and levellers included. Total thickness depending on components: 13, 16, 19 or 30 mm.
- Shelves:
  - In hardboard: 600 mm wide and 19 mm thick edged as on rest of the design with 2 mm thick edging.
  - In steel plate: 600 or 1,200 mm wide steel plate. Colour of choice.  
Option: filing drawer support.
  - In hardboard for bookshelf modules: 600 and 1,200 mm wide and 30 mm thick.
- Sliding, smooth and solid door leaves in woodchip hardboard, edged and with the same coating options as the panels; or glazed leaves with aluminium frame. Total thickness: 19 mm.  
Option: glass door for bookshelf modules.

### Frame

- Telescopic bottom runner and top runner in Sendzimir galvanised steel.
- Quality in accordance with european standard EN 10142-A1:1994 (DX51D+Z).

### Paintwork

- Previously degreased.
- Electrostatically coated with polyester powder or polyester epoxy and polymerised in furnace at 200°C.
- Average paint coat thickness: 50/60 microns.
- Colour tolerance: DIN 5033 standard.

### Fittings

- Demountable, triple-position hinges in same nickel plate finish as shelf supports. Other fittings treated with the same paint, zinc, anodised coating, etc. as required.
- File drawers and telescopic, extractable drawers. Measurements 600 and 1,200 mm.

## Performances





### Demountability and re-installation

- Complete, independent demountability of all modules thanks to independent assembly and fixture systems for each assembly component.
- Total module and component re-installation and interchangeability.

## Dynamobel Quality


All the processes used in the design, production, distribution and sale of DYNAMOBEL's storage wall system are quality assurance certified by LLOYD'S per EN ISO 9001:2000.

### Standard modules



(e) Option: module without stud and with metallic shelves  
 \* Option: glazed door leaves


### Standard modules




## Standard modules: horizontal sections

### Modules


#### With back



#### With hidden back




#### Without back




## Standard modules: horizontal sections

### Wall start


With back



With hidden back




Without back




### Terminal


With back



With hidden back




Without back




### Corner module

With back



With hidden back



Without back

