YES
WORK CHAIR

TECHNICAL SHEETS

FEATURES

OPTIONS

Armrest

- Height adjustment 75 mm, 7 positions (**4D**: 100 mm, 9 positions)
- Depth adjustment: (**2D**: 55 mm)
- Rotating adjustment **4D**: 20º (-10º, 0º, +10º)
- Width adjustment 25 mm.

Height adjustment 1D 2D 4D | Depth adjustment 2D 4D | Rotating adjustment 4D | Width adjustment 4D

DIMENSIONS

kg	Weight in kg	13,5
Ta	Seat fabric	0,65 ml (2 uds.)
Tr	Backrest fabric	0,6 ml (2 uds.)
Tc	Headrest fabric	0,01 ml

YES
WORK CHAIR

TECHNICAL SHEETS

DESCRIPCIÓN

BACKREST

Height adjustable 75 mm with 12 positions (zipper regulation). Reclining angle up to 21º.

Option lumbar support on mesh backrest, adjustable in depth 22 mm with 4 positions.

Option headrest 65 mm height adjustable with 8 positions, and 36º rotation with 4 positions.

Mesh backrest: Perimeter frame with "Y" shaped ribs, made of highly resistant and flexible polyamide, fixed directly to the support-backrest in steel. The tension of the mesh allows a correct support and adaptation of the backrest to the anatomy of the user's back. It does not deform. fabric feel.

Upholstered backrest: It is an ergonomically shaped injection molded polypropylene piece, highly resistant and flexible, fixed directly to the support-backrest in steel. Flexible rubber foam with a 30 mm thickness and a 30 kg/m³ density, onto which the fabric is fitted.

SEAT

Adjustable in depth 70 mm with 8 positions.

Injection polypropylene support with ergonomically shaped fiber, plus flexible foam rubber with a thickness of 45 mm and a density of 40 kg/m³, onto which the fabric is fitted.

MECHANISM

Self-weighing synchro mechanism.

It can be locked in 5 position or permanent contact with non-return system.

BASE

Polyamide with fiber: Ø 680 mm, black finish.

Aluminum: Ø 700 mm, polished or painted epoxy polyester.

Soft and hard floor castors Ø 60, black color.

Option conductive castor Ø 60.

ARMRESTS

▲ ARMREST 1D, NE or BA

▲ ARMREST 2D, NE or BA

▲ ARMREST 4D, NE

RECYCLABILITY RATE

94,97 %

CERTIFICATIONS AND STANDARDS

UNE EN 1335