




## ZAS BENCHES




### DIMENSIONS


1 • Bench 2 places



2 • Bench 3 places



3 • Bench 4 places



	• 1 •	• 2 •	• 3 •
p Seat depth	46,00	46,00	46,00
P Total depth	55,70	55,70	55,70
Ta Seat fabric	1,40	2,10	2,80
Tr Backrest fabric	1,40	2,10	2,80
Pa Seat leather	1,68	2,52	3,36
Pr Backrest leather	1,68	2,52	3,36



### FEATURES AND OPTIONS



Painted epoxy polyester base

- Variability in number of seats
- Optional upholstered seat
- Optional upholstered seat and backrest
- Optional fixed to the floor

# TECHNICAL SHEETS



### DESCRIPTION

#### BACKREST

In injected polypropylene with an ergonomic shape, and with aesthetic grooves that facilitate its flexibility and give it a special characteristic. It is joined to the structure of the bench by a back support made of injected aluminium.

Optionally, it will have a block foam onto which the fabric is fitted.

#### SEAT

In injected polypropylene, with an ergonomic shape, fastened to the seat support plates by 4 screws.

Optionally, it will have a block foam onto which the fabric is fitted.

#### STRUCTURE

Longitudinal frame formed by an oval tube of St42 80x30x3 steel, shaped at the ends to Ø30. 3mm thick FePO3 seat support plates welded by injection to the longitudinal tube.

Injected aluminum legs fixed to the longitudinal frame at the ends.



### CERTIFICATIONS AND STANDARDS



EN 11012  
EN 11021  
EN 11022